

CFORCE 1000 OVERLAND 2025

Forest Green Desert Tan



**The most equipped vehicles
on the market**
More than \$5,600 in add-ons!

Standard features and benefits

Removable rear cargo box
Storage capacity of 105 L
\$600 value

Skid plate assembly
\$1,050 value

3,500 lbs winch
(complete assembly)
\$1,000 value

High strength aluminum
winch armor
\$100 value

Hand guard assembly
with windshield
\$300 value

Aluminium rims with
14" retaining ring
\$1,800 value

LED light bar
\$500 value

5-year CFMOTO warranty

Safety and convenience package

Including:

- LED lights
- Side mirrors
- Hand protector
- Retaining bars for passenger
- Trailer connector
- USB port
- 12 V outlet
- Turn signals
- Horn

\$750 value

BEST
5
YEAR
LIMITED WARRANTY

5 Year limited warranty:
1 year complete with no mileage
restriction + 48 months balance
powertrain only or 5,000 km



Hydraulic Shock
Absorber With 5 Spring
Preload Adjustment



Electric Power
steering



CV-Tech IBC
clutch system

Specifications

Engine

Type: V-Twin cylinder, liquid-cooled,
SOHC, 8-valves, 4-strokes

Displacement: 963 cc

Bore & Stroke:
91 x 74 mm (3.58 x 2.9 in)

Compression: 10.8: 1

Engine management:
Fuel injected engine

Cooling system: Liquid

Starting: Electric

Battery: 30 Ah

Size / weight

Length x Width x Height:
2435 x 1264 x 1605 mm
(95.8 x 49.7 x 63.1 in)

Wheelbase: 1480 mm (58.3 in)

Ground clearance: 300 mm (11.8 in)

Minimum turning radius:
3500 mm (137.7 in)

Fuel tank capacity: 26 L (6.8 gal)

Curb weight: 500 kg (1102 lbs)

Towing capacity: 800 kg (1764 lbs)

Rear box capacity (Front/Rear):

Front 45 kg (99 lbs)

Rear 90 kg (198 lbs)

Brakes

Four wheel brake disc

Wheels

Front wheels: Aluminum alloy (14 in)

Rear wheels: Aluminum alloy (14 in)

Front tires: AT 27 x 9-14

Rear tires: AT 27 x 11-14

Transmission

Clutch: OmniDrive™ CVT

Gear box: P / R / N / H / L
(parking lock shift system)

Power train: 2WD / 4WD,
electric locking differential

Suspension and steering

Front suspension: Double A-arm
independent, gas shock absorber
with adjustable rebound/
compression

Front travel: 225 mm (8.8 in)

Rear suspension: Independent
trailing arm, fully adjustable,
gas shocks

Rear travel: 225 mm (8.8 in)

Steering: Triple-mode Electric Power
Steering (EPS)

Protection plan

EASY protection plan available

EASY | PROTECTION
PLAN

Follow us



cfmoto.ca

*The pictures are for illustrative purposes only and accessories shown are not included. Specifications to change without notice. Details in store.