CFORCE 800 TOURING 2026











More than \$3,350 in add-ons!

Standard features and benefits

Rims **\$1,500 value**

Trailer hitch \$100 value

5-year CFMOTO warranty

3,500 lbs winch (complete assembly) \$1,000 value

Safety and convenience package

Including:

- Side mirrors
- Hand protectors
- Retaining bars for passenger
- Trailer connector
- Anti-theft device (gear lever lock)
- USB port
- 12 V outlet
- Turn signals
- Horn

\$750 value





Hydraulic Shock Absorber With 5 Spring Preload Adjustment





CV-Tech IBO

Specifications

Engine

Type: V-Twin cylinder, liquid-cooled, SOHC, 8-valves, 4-strokes

Displacement: 800 cc

Bore & Stroke:

91 x 61.5 mm (3.58 x 2.4 in)

Compression: 10.8:1

Engine management:

Fuel injected engine

Cooling system: Liquid

Starting: Electric

Battery: 30 Ah

Size / weight

Length x Width x Height: 2345 x 1264 x 1450 mm

(92.3 x 49.7 x 57 in)

Wheelbase: 1480 mm (58.3 in)

Ground clearance: 285 mm (11.2 in)

Minimum turning radius:

3500 mm (137.7 in)

Fuel tank capacity: 26 L (6.8 gal)

Curb weight: 458 kg (1010 lbs)

Towing capacity: 800 kg (1764 lbs)

Rack capacity (Front/Rear):

Front 45 kg (99 lbs) Rear 90 kg (198 lbs)

Brakes

Four wheel brake disc

Wheels

Front wheels: Aluminum alloy (14 in)
Rear wheels: Aluminum alloy (14 in)

Front tires: 26 x 8-14
Rear tires: 26 x 10-14

Transmission

Clutch: OmniDrive™ CVT

Gear box: P/R/N/H/L (parking lock shift system)

Power train: 2WD / 4WD, electric locking differential

Suspension and steering

Front suspension: Double A-arm independent, gas shock absorber with adjustable rebound/compression

Front travel: 225 mm (8.8 in)

Rear suspension: Independent trailing arm, fully adjustable, gas shocks

Rear travel: 225 mm (8.8 in)

Steering: Electronic Power Steering

Protection plan

EASY protection plan available





5 Year limited warranty: 1 year complete with no mileage restriction + 48 months balance powertrain only or 5,000 km



