# **CFORCE** 1000 MV 2026







More than \$6,430 in added value!

Standard features and benefits

14-inch Beadlock rims \$1,800 value

Snorkel, Higher air filter & Radiator relocator \$1,600 value

3,500 lbs winch \$1,000 value

**HDPE Skid Plate for the** underside of vehicle \$750 value

Front and rear bumpers \$700 value

Cargo box \$380 value

Wider fender \$200 value

6-month CFMOTO warranty







# **Specifications**

## Engine

Type: V-Twin cylinder, liquid-cooled, SOHC, 8-valves, 4-strokes

Displacement: 963 cc Bore & Stroke:

91 x 74 mm (3.58 x 2.9 in)

Compression: 10.8: 1 **Engine management:** 

Fuel injected engine Cooling system: Liquid

Starting: Electric Battery: 30 Ah

# Size / weight

Length x Width x Height:

2491 x 1370 x 1390 mm (98.1 x 53.9 x 54.7 in)

Wheelbase: 1480 mm (58.3 in) Ground clearance: 334 mm (13.1 in)

Minimum turning radius:

3800 mm (149.6 in) Fuel tank capacity: 26 L (6.8 gal)

Curb weight: 522 kg (1150 lbs) Towing capacity: 820 kg (1800 lb)

Rack capacity (Front/Rear): Front 20 kg (44.1 lbs)

Rear 90 kg (198 lbs)

#### **Brakes**

Hydraulic brake

### Wheels

Front wheels: Aluminum alloy (14 in) Rear wheels: Aluminum alloy (14 in)

Front tires: 30 x 9-14 Rear tires: 30 x 10-14

#### **Transmission**

Clutch: OmniDrive™ CVT Gear box: P/R/N/H/L (parking lock shift system)

Power train: 2WD / 4WD, electric locking differential

# Suspension and steering

Front suspension: Double A-arm independent, gas shock absorber with adjustable rebound/ compression

Front travel: 185 mm (7.3 in)

Rear suspension: Independent trailing arm, fully adjustable, gas shocks

Rear travel: 236 mm (9.3 in)

Steering: Triple-mode Electric Power

Steering (EPS)







