UFORCE600 2026







The most equipped vehicles on the market

More than \$3,800 in add-ons!

Standard features and benefits

Rims \$1,200 value

Trailer hitch \$100 value

Roof \$500 value

3,500 lbs winch (complete assembly) \$1,000 value

5-year CFMOTO warranty

Safety and convenience package

Including:

- Side mirrors
- Retaining bars for passenger
- 12 V outlet
- Turn signals
- Horn

\$1,000 value

Specifications

Engine

Type: Single-cylinder, liquid cooled, SOHC, 4-valves, 4-strokes

Displacement: 580 cc

Bore & Stroke:

91 x 89.2 mm (3.6 x 3.5 in)

Compression: 10.68: 1

Engine management: Fuel injected engine

Cooling system: Liquid

Starting: Electric

Battery: 30 Ah

Size / weight

Length x Width x Height: 2820 x 1470 x 1950 mm

(111 x 57.9 x 76.8 in)

Wheelbase: 1950 mm (76.8 in)

Ground clearance: 270 mm (10.6 in)

Minumum turning radius:

4750 mm (187 in)

Fuel tank capacity: 35 L (9.25 gal)

Curb weight: 644 kg (1420 lbs)

Payload capacity: 483 kg (1065 lbs)

Towing capacity: 680 kg (1499 lbs)

Rear cargo box capacity:

250 kg (551.2 lbs)

Brakes

Four wheel brake disc

Wheels

Front wheels:

Aluminum alloy (12 in)

Rear wheels:

Aluminum alloy (12 in)

Front tires: 26 x 9-12

Rear tires: 26 x 10-12

Transmission

CV-Tech IBC clutch system:

Variable transmission

Gear box: P/R/N/H/L

(parking lock shift system)

Power train: 2WD / 4WD,

locking front differential

Suspension and steering

Front suspension: Double A-arm independent, hydraulic shock

absorber

Front travel: 200 mm (7.87 in)

 $\textbf{Rear suspension:} \ \mathsf{Double} \ \mathsf{A}\text{-}\mathsf{arm}$

independent, hydraulic shock

absorber

Rear travel: 200 mm (7.87 in)

Steering:

Electric Power Steering (EPS)

Protection plan

EASY protection plan available





5 Year limited warranty: 1 year complete with no mileage restriction + 48 months balance powertrain only or 5,000 km



