UFORCE 800 XL 2026









More than \$3,800 in add-ons!

Standard features and benefits

Rims \$1.200 value

Trailer hitch \$100 value

Roof \$500 value

4,500 lbs winch (complete assembly) \$1,000 value

5-year CFMOTO warranty

Safety and convenience package

Including:

- Side mirrors
- Retaining bars for passenger
- 12 V outlet
- Turn signals
- Horn

\$1,000 value

Specifications

Engine

Type: V-Twin cylinder, liquid cooled, SOHC, 8-valves, 4-strokes

Displacement: 800 cc

Bore & Stroke:

91 x 61.5 mm (3.6 x 2.4 in)

Compression: 10.8: 1

Engine management:

Fuel injected engine

Cooling system: Liquid

Starting: Electric

Battery: 28 Ah

Size / weight

Length x Width x Height: 3635 x 1525 x 2007 mm

(143.1 x 60 x 79 in)

Wheelbase: 2770 mm (109 in)

Ground clearance: 300 mm (11.8 in)

Minimum turning radius:

5600 mm (220.4 in)

Fuel tank capacity: 40 L (10.57 gal)

Curb weight: 773 kg (1704 lbs)

Payload capacity: 680 kg (1499.1 lbs)

Towing capacity: 680 kg (1499.1 lbs)

Rear cargo box capacity: 300 kg (661.3 lbs)

Brakes

Four wheel hydraulic disc brake

Wheels

Front wheels:

Aluminum alloy (14 in)

Rear wheels:

Aluminum alloy (14 in)

Front tires: 27 x 9-14

Rear tires: 27 x 11-14

Transmission

Clutch: OmniDrive™ CVT

Gear box: P/R/N/H/L (parking lock shift system)

Power train: 2WD / 4WD, locking front differential

Suspension and steering

Front suspension: Double A-arm independent, hydraulic shock

absorber

Front travel: 225 mm (8.86 in)

Rear suspension: Double A-arm independent with sway bar, hydraulic shock absorber

Rear travel: 225 mm (8.86 in)

Steering:

Electric Power Steering (EPS)

Protection plan

EASY protection plan available





restriction + 48 months balance powertrain only or 5,000 km



