

UFORCE U10 PRO HIGHLAND 2026

 Bordeaux Red
 Nebula Black
 True Timber Kanati



**The most equipped vehicles
on the market**

More than \$15,150 in add-ons!

Standard features and benefits

Rims
\$1,200 value

Rear windshield
\$850 value

Heater / air conditioning
3,500 value

Trailer hitch
\$100 value

Roof
\$500 value

**4,500 lbs winch
(complete assembly)**
\$1,000 value

**Tilting front windshield
and wiper**
\$2,000 value

Audio system and speakers
\$1,000 value

5-year CFMOTO warranty

**Doors with
electrical windows**
\$4,000 value

**Safety and convenience
package**
Including:
– Side mirrors
– Retaining bars
for passenger
– 12 V outlet
– Turn signals
– Horn
\$1,000 value

BEST
5 YEAR
LIMITED WARRANTY

5 Year limited warranty:
1 year complete with no mileage
restriction + 48 months balance
powertrain only or 5,000 km



Electric Power
Steering



12 V
outlet

Specifications

Engine

Type: 3 cylinder, liquid-cooled,
DOHC, 12-valves, 4-strokes

Displacement: 998 cc

Bore & Stroke:
80 x 66.2 mm (3.15 x 2.61 in)

Compression: 11.0: 1

Engine management:
Fuel injected engine

Cooling system: Liquid

Starting: Electric

Battery: 30 Ah

Size / weight

Length x Width x Height:
2965 x 1645 x 1945 mm
(116.7 x 64.7 x 76.5 in)

Wheelbase: 2060 mm (81.1 in)

Ground clearance: 330 mm (12.9 in)

Minimum turning radius:
4250 mm (167.3 in)

Fuel tank capacity: 45 L (11.8 gal)

Dry weight: 790 kg (1742 lbs)
(134 kg accessories)

Payload capacity: 727 kg (1602 lbs)

Towing capacity: 1134 kg (2499 lbs)

Rear cargo box capacity:
454 kg (1000 lbs)

Brakes

Four wheel brake disc

Special features

CFMOTO Ride app connectivity

Wheels

Front wheels: Aluminum alloy (14 in)

Rear wheels: Aluminum alloy (14 in)

Front tires: 29 x 9-14

Rear tires: 29 x 11-14

Transmission

Clutch: OmniDrive™ CVT

Gear box: P / R / N / H / L
(parking lock shift system)

Power train: 2WD / 4WD,
locking front differential

Suspension and steering

Front suspension: Double A-arm
independent, hydraulic shock
absorber

Front travel: 280 mm (11 in)

Rear suspension: Double A-arm
independent, hydraulic shock
absorber

Rear travel: 260 mm (10.2 in)

Steering:
Electric Power Steering (EPS)

Protection plan

EASY protection plan available

EASY | **PROTECTION**
PLAN

Follow us



cfmoto.ca

*The pictures are for illustrative purposes only and accessories shown are not included. Specifications to change without notice. Details in store.