Getting lost in the woods





CFORCE 400 EPS LX 1UP 2023

Available colours



Free More than \$4,000 in free add-ons!

The most equipped vehicles on the market

Standard features and benefits

Trailer hitch \$103 value

5-year CFMOTO warranty \$3 300 value

2,500 Lbs winch (complete assembly) \$484 value

Safety and convenience package

Including:

- Side mirrors
- Trailer hitch
- Double USB port
- 12V outlet
- Flashers
- Horn

\$283 value



5 Year limited warranty: 1 year complete with no milage restriction + 48 months balance powertrain only or 5,000 km

Starting at \$7,899*









Electric-power steering



Side



Cvtech clutch system

Fuel injected

Specifications

Motor

Type: Single-Cylinder, liquid-cooled, 4-valves, 4-strokes

Displacement: 400 cc

Bore & Stroke: 91 x 61.5 mm

(3.58 x 2.42 in)

Compression: 10.3: 1

Engine management: Fuel injected

Cooling system: Liquid

Starting: Electric

Battery: 30 Amp

Size / weight

Length x width x height: 2046 x 1125 x 1150 mm (80.6 x 44.3 x 45.3 in)

Wheelbase: 1260 mm (49.6 in)

Ground clearance: 250 mm (9.8 in)

Minimum turning radius:

2800 mm (113.3 in)

Fuel tank capaity: 17 L (4,5 gal)

Net weight: 332 kg (732 lbs)

Towing capacity: 612 kg (1349 lbs)

Payload capacity: 170 kg (375 lbs)

Rack capacity:

Front 30 kg (66 lbs)

Rear 60kg (132 lbs)

Brakes

Front axles: Double-disc Rear axles: Single-disc

Wheels

Front wheels: Aluminum alloy wheels (12 x 6 in)

Rear wheels: Aluminum alloy wheels (12 x 7.5 in)

Front tires: AT 25 x 8-12

Rear tires: AT 25 x 10-12

Transmission

CV-Tech IBC clutch system: variable transmission.

Gear box: L/H/N/R/P (parking

lock shift system)

Power train: 2WD / 4WD, electric

locking differential

Suspension and direction

Front suspension: Double arched

A-arm independant

Front travel: 190 mm (7.5 in)

Rear suspension: Double A-arm

independant

Rear travel: 225 mm (8.9 in)

Steering: Electronic Power Steering







