



CFORCE 600 **TOURING** 2024 CF600AZ-3LA

Available

colours





More than \$2,800 in add-ons!

Standard features and benefits

Rims \$1,200 value

Trailer hitch \$100 value

5-year CFMOTO warranty

3,500 lbs winch (complete assembly) \$750 value

Safety and convenience package

Including:

- Side mirrors
- Hand protector
- USB port
- 12V outlet
- Lead headlight with integrated turn signals
- Horn

\$750 value



5 Year limited warranty: 1 year complete with no milage restriction + 48 months balance powertrain only or 5,000 km









Specifications

Motor

Type: Single-Cylinder, liquid-cooled,

4-valves, 4-strokes Displacement: 580 cc

Bore & Stroke:

91 x 89.2 mm (3.58 x 3.5 in)

Compression: 10.7:1

Engine management:

Fuel injected engine

Cooling system: Liquid Starting: Electric

Battery: 30 Ah

Size / weight

Length x Width x Height: 2235 x 1180 x 1390 mm

(88 x 46.5 x 54.7 in)

Wheelbase: 1480 mm (58.3 in)

Ground clearance: 270 mm (10.6 in)

Minimum turning Radius:

3700 mm (145.7 in)

Fuel tank capacity: 18 L (4.76 gal)

Net weight: 415 kg (915 lbs)

Towing capacity: 680 kg (1499 lbs)

Payload capacity: 220 kg (485 lbs) Rack capacity (Front/Rear):

20 kg (44 lbs) / 40 kg (88 lbs)

Brakes

Four wheel hydraulic disc + rear wheel parking

Wheels

Front wheels:

Aluminium alloy (12 in)

Rear wheels:

Aluminium alloy (12 in)

Front tires: AT 25 x 8-12

Rear tires: AT 25 x 10-12

Transmission

CV-Tech IBC clutch system:

Variable transmission

Gearbox: L/H/N/R/P

(parking lock shift system) Power train: 2WD / 4WD, electric

locking differential

Suspension and direction

Front suspension:

Double A-arm independant

Front travel: 160 mm (6.3 in)

Rear suspension: Double A-arm

independant

Rear travel: 210 mm (8.3 in)

Steering:

Electonic Power Steering (EPS)

Protection plan

EASY protection plan available









