



CFORCE 400 2024 **CF400AZ-6S**

Available colours



The most equipped vehicles on the market

More than \$2,800 in add-ons!

Standard features and benefits

Rims \$1,200 value

Trailer hitch \$100 value

5-year CFMOTO warranty

2,500 lbs winch (complete assembly) \$750 value

Safety and convenience package

Including:

- Side mirrors
- Trailer connector
- USB port
- Turn signals
- Horn

\$750 value



5 Year limited warranty: 1 year complete with no milage restriction + 48 months balance powertrain only or 5,000 km





4-Wheels Drive



Cvtech clutch system



Specifications

Motor

Type: Single-Cylinder, liquid-cooled, 4-valves, 4-strokes

Displacement: 400 cc

Bore & Stroke: 91 x 61.5 mm

(3.58 x 2.42 in)

Compression: 10.3: 1

Engine management: Fuel injected

Cooling system: Liquid

Starting: Electric

Battery: 30 Ah

Size / weight

Length x width x height:

2046 x 1125 x 1150 mm

(80.6 x 44.3 x 45.3 in)

Wheelbase: 1260 mm (49.6 in)

Ground clearance: 250 mm (9.8 in)

Minimum turning radius:

2800 mm (110.2 in)

Fuel tank capaity: 17 L (4,5 gal)

Net weight: 332 kg (732 lbs)

Towing capacity: 612 kg (1349 lbs)

Payload capacity: 170 kg (375 lbs)

Rack capacity:

Front 30 kg (66 lbs)

Rear 60kg (132 lbs)

Brakes

Three wheels hydraulic disc + rear wheel parking

Wheels

Front wheels: Aluminum alloy wheels

Rear wheels: Aluminum alloy wheels

(12 in)

Front tires: AT 25 x 8-12 Rear tires: AT 25 x 10-12

Transmission

CV-Tech IBC clutch system: variable

Gear box: L/H/N/R/P (parking

lock shift system)

Power train: 2WD / 4WD, electric

locking differential

Suspension and direction

Front suspension: Double arched

A-arm independant

Front travel: 190 mm (7.5 in)

Rear suspension: Double A-arm

independant

Rear travel: 225 mm (8.9 in)

Steering: Electronic Power Steering

Protection plan

EASY protection plan available











