



CFORCE 500 2024 CF500AZ-10S

Available colours









More than \$2,800 in add-ons!

Standard features and benefits

Rims \$1,200 value

Trailer hitch \$100 value

5-year CFMOTO warranty

2,500 lbs winch (complete assembly) \$750 value

Safety and convenience package

Including:

- Side mirrors
- Trailer connector
- Anti-theft device (gear lever lock)
- USB port
- 12V outlet
- Turn signals
- Horn

\$750 value



5 Year limited warranty 1 year complete with no milage restriction + 48 months balance powertrain only or 5,000 km









Specifications

Motor

Type: Single-Cylinder, liquid-cooled, 4-valves, 4-strokes

Displacement: 495 cc

Bore & Stroke:

91 x 76.5 mm (3.58 x 3.01 in)

Compression: 10.3: 1

Engine management:

Fuel injected engine

Cooling system: Liquid

Starting: Electric

Battery: 30 Ah

Size / weight

Length x width x height:

2046 x 1125 x 1150 mm

(80.6 x 44.3 x 45.3 in)

Wheelbase: 1260 mm (50 in)

Ground clearance: 262 mm (10 in)

Minimum turning radius:

2800 mm (110.2 in)

Fuel tank capacity: 17 L (4.5 gal)

Net weight: 355 kg (782 lbs)

Towing capacity: 612 kg (1349 lbs)

Payload capacity: 170 kg (375 lbs)

Rack capacity (Front/Rear):

30 kg (66 lbs) / 60 kg (132 lbs)

Brakes

Three wheel hydraulic disc + rear wheel parking

Wheels

Front wheels:

Aluminum wheels alloy (12 in)

Rear wheels:

Aluminum wheels alloy (12 in)

Front tires: AT 25 x 8-12 Rear tires: AT $25 \times 10-12$

Transmission

CV-Tech IBC clutch system: variable

transmission.

Gearbox: L/H/N/R/P (parking lock shift system)

Power train: 2WD/ 4WD, electric

locking differential

Suspension and direction

Front suspension: Double arched

A-arm independant

Front travel: 190 mm (7.5 in)

Rear suspension:

Double A-arm independant

Rear travel: 225 mm (8.9 in)

Steering:

Electronic Power Steering (EPS)

Protection plan

EASY protection plan available











