



# **UFORCE** 1000 XL 2024 CF1000UZ-2

Available colours







More than \$3,800 in add-ons!

Standard features and benefits

Rims \$1,200 value

Trailer hitch \$100 value

Roof \$500 value

3,500 lbs winch (complete assembly) \$1,000 value

5-year CFMOTO warranty

Safety and convenience package

Including:

- Side mirrors
- Retaining bars for passenger
- 12V outlet
- Turn signals
- Horn

\$1,000 value



5 Year limited warranty: 1 year complete with no milage restriction + 48 months balance powertrain only or 5,000 km









# **Specifications**

### Motor

Type: V-Twin Cylinder, liquid cooled, SOHC, 4-stroke, 8-valve

Displacement: 963 cc

Bore & Stroke:

91 x 74 mm (3.6 x 2.9 in)

Compression: 10.6:1

**Engine management:** 

Fuel injected engine

Cooling system: Liquid

Starting: Electric

Battery: 30 Ah

# Size / weight

Length x width x height: 3745 x 1615 x 1850 mm (147.5 x 63.5 x 72.8 in)

Wheelbase: 2850 mm (112.2 in)

Minimum ground clearance:

310 mm (12 in)

Minimum turning radius:

5500 mm (216.5 in)

Fuel tank capacity: 40 L (10.6 gal)

Net weight: 870 kg (1829.8 lbs)

Payload capacity: 660 kg (1455 lbs)

Rear cargo capacity: 350 kg (770.9 lbs)

#### **Brakes**

Four wheel hydraulic brake system

## Wheels

Front wheels:

Aluminum alloy  $(14 \times 7 \text{ in})$ 

Rear wheels:

Aluminum alloy (14 x 8 in)

Front tires: AT 27 x 9-14 Rear tires: AT 27 x 11-14

#### **Transmission**

CV-Tech IBC clutch system: variable transmission

Gear box: L/H/N/R/P

(parking lock shift system)

Power train: 2WD / 4WD, locking

front differential

Rear differential: Mechanical

auto-lock differential NEW

## Suspension and direction

Front suspension: Double A-arm independent suspension, hydraulic shock absorber

Front travel: 260 mm (10.2 in)

Rear suspension: Double A-arm independent suspension, hydraulic shock absorber

Rear travel: 220 mm (8.6 in)

Steering: Electric Power Steering

## Protection plan

EASY protection plan available







